



Stainless steel tote tanks:



Nominal Capacity = 350 gal (1298L)
Nominal Length = 42" (1066 mm)
Nominal Width = 48" (1219 mm)
Nominal Height = 51" (1295 mm)
Approx. Tare Weight = 475 lbs (215kg)
Max Gross Weight = 6017 lbs (2735 kg)

Stainless steel tote tanks are an efficient, sensible alternative to 55-gallon drums for the shipping and storing of most liquids. They're built to UN specifications, and standard designs feature 10-gauge construction throughout, and a sloped bottom for virtually complete drainage. One 550-gallon tote tank replaces ten drums, minimizing the amount of handling required which lowers the risk of handling accidents. They are refillable and durable.

Feature (a): 3" metal or poly combination filling cap and fusible vent. Benefit: Cover can remain sealed during filling.

Feature (b): 22" EPDM gasket, zinc-plated bolted clamp ring, formed neck.

Feature (c): 2" top fill bung with Buna-N gasket. Benefit: Optional accessories.

Feature (d): Informational decals. Benefit: Safety.

Feature (e): 6 1/2" high, radius corner legs with caps. Benefit: Designed to avoid catching on floor obstructions.

Feature (f): 2" bottom discharge assembly, comprising: 316 ss three-piece valve assembly with locking handle ball valve, plastic valve plug.

Feature (g): Sloped bottom. Benefit: Facilitates virtually complete drainage.

Feature (h): 304 stainless steel w/2B Finish. 10-gauge construction throughout. Benefit: Durable and rust resistant.

Feature (i): UN markings. Benefit: Worldwide recognition and compliance.

Feature (j): Heavy-duty lifting lugs and leg positioners. Benefit: Easy stacking and lifting.

Feature (k): 22 5/16" top opening. Benefit: Easy cleaning.

Feature (l): Label (includes serial number).

Full-length winged valve guard.

UN 31A Qualified on 350-gallon and 550-gallon sizes.

UN and DOT Qualifications

DOT UN31A permits shipment of flammable and combustible liquids authorized by Title 49 CFR. Allowable modes of transportation: motor vehicle, rail freight, cargo vessel, or air freight. NMFC Item 41032, Sub 1, Class 125.

Pacific Northwest Equipment Inc.
7701 South 200th ST.
Kent, WA 98032
1-800-659-0147